

Self-aligning pads, adjustable, with O-ring and hexagon socket Form K, flattened POM ball smooth

Item description/product images



Description

Material:

Body carbon steel.
Ball Form K POM.

Version:

Body tempered.
POM ball white.

Note:



Self-aligning pads are used to support and clamp unmachined and machined workpieces.
They can also be used as stops, supports and thrust pads in fixtures and toolmaking.

Ball secured against rotation.

Advantages:

The built-in O-ring holds the ball in place and keeps dirt and foreign particles out, ensuring uniform movement.
The hexagon socket allows easy adjustment and positioning in through holes.

Drawings



Self-aligning pads, adjustable, with O-ring and hexagon socket Form K, flattened POM ball smooth

Overview of items

Order No.	Form	B	D2	D3	H1	SW1	Ball-Ø	Load rating max. kN (static load only)
K0290.712X025	K	25	M12	6	1,5	6	7	2
K0290.712X035	K	35	M12	6	1,5	6	7	2
K0290.712X050	K	50	M12	6	1,5	6	7	2
K0290.716X025	K	25	M16	8,5	1,5	8	10	4
K0290.716X035	K	35	M16	8,5	1,5	8	10	4
K0290.716X050	K	50	M16	8,5	1,5	8	10	4